

# REPORT DOCUMENTATION PAGE

AFRL-SR-AR-TR-06-0013

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)

2. REPORT DATE 30 Sep 2005

3. REPORT TYPE AND DATES COVERED  
Final; 01 Jan 2005—31 Aug 2005

4. TITLE AND SUBTITLE

Electronic Terahertz Spectroscopic Imaging of Explosives and Weapons

5. FUNDING NUMBERS

F49620-02-1-0329

6. AUTHOR(S)

D. W. van der Weide (Principal Investigator)

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

University of Wisconsin-Madison  
1415 Engineering Dr  
Madison WI 53706

8. PERFORMING ORGANIZATION  
REPORT NUMBER

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Lt. Col. Gernot Pomrenke  
Air Force Office of Scientific Research  
4015 Wilson Boulevard, Room 713  
Arlington, VA 22203-1954

10. SPONSORING / MONITORING  
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Air Force position, policy or decision, unless so designated by other documentation.

12 a. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

12 b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

We seek to build imaging arrays for screening personnel through portals using new microwave circuits that produce coherent signals for electronic terahertz (THz) generation and detection integrated circuits. Since we have demonstrated that these circuits can distinguish reflection signatures of a variety of threats from those of clothing and skin, they can be used for screening human subjects working in conjunction with established metal screening portals, which will provide a completely new measure of threat imaging and hence security.

We developed a broadband electronic THz system capable of reflection and transmission spectroscopy of materials. We also developed broadband antennas with nearly 20 dB of gain that can be integrated with such THz systems.

14. SUBJECT TERMS

Electronic terahertz techniques, gas spectroscopy, reflection spectroscopy, nonlinear transmission lines, samplers, coherent measurements, dual source interferometer

15. NUMBER OF PAGES

16. PRICE CODE

17. SECURITY CLASSIFICATION  
OR REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION  
ON THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION  
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UL

NSN 7540-01-280-5500

Standard Form 298 (Rev.2-89)  
Prescribed by ANSI Std. Z39-18

298-102

20060131 290

---

**REPORT DOCUMENTATION PAGE (SF298)**  
**(Continuation Sheet)**

---

**Objectives**

The objectives of this work were to advance the state of electronic pulsed terahertz systems to broadband dielectric reflection measurements of important energetic materials and plastic weapons in the 1–1000 GHz regime using integrated-circuit nonlinear transmission lines and antennas as generators of this radiation. Previous work from our lab had already demonstrated spectral signatures from a variety of threats, including bacterial spores of various strains[1-5].

**Status of effort**

The project is completed.

**Accomplishments/New Findings**

We built several pulsed THz spectroscopy systems using GaAs nonlinear transmission lines (Figure 1), and we conducted and published data from transmission and reflection experiments on a variety of materials, including biological materials, such as anthrax simulants (bacillus cereus [B. cereus], B. globigii, and B. thurengiensis), both wild-type and mutant strains (Figure 2) [1-5]. We obtained sample collection and particle concentration technology from MicroEnergy Technologies, Vancouver WA, for some of this work.

We also focused on reducing the cost of our technology by developing circuits that promote integrating the coherent oscillators and amplifiers needed to drive the pulsing circuitry. This will open the door to eventual integration of our technology into familiar metal-detection portals, which we consider a major potential advantage of our approach over that of other screening technologies.

An extremely important factor in advancing spectroscopic imaging is the ability to suppress standing-wave phenomena. With a startup company, Tera-X, we developed modulation techniques to minimize the effects of standing waves in broadband THz spectra, and also developed manufacturable ultrawideband (UWB) antennas that exhibit nearly 20 dB of gain and can be scaled to the THz regime. Broadband sensing and spectroscopic imaging using both reflection and transmission in the 1-1000 GHz regime can be done with pulsed terahertz (THz) circuits, such as nonlinear transmission lines (NLTs)[6-10]. Yet some of the most significant limitations of any time-domain THz system—whether purely electronic or optoelectronic—arise from the lack of amplifiers, whether power or low-noise. To address this pressing need, we develop ultrawideband antennas that have greater gain and better polarization characteristics than the planar antennas used in today's THz systems. Many concepts imported from lower-frequency UWB systems are valid for the THz regime, as well.

We take two approaches to these coherent measurements: (1) using a conventional source/detector arrangement with sampling detectors or (2) spatially combining the freely propagating beams from two matched picosecond pulse generators. The latter method employs a dual-source interferometer (DSI) modulating each harmonic of one source with a precisely-offset harmonic from the other source—both sources being driven with stable phase-locked synthesizers—the resultant beat frequency can be low enough for detection by a standard bolometer. Room-temperature detection possibilities for the DSI include antenna-coupled Schottky diodes.

This year, using the reflection configuration, we have measured absorption characteristics of a variety of targets, including bacillus spores collected on optical micropillars (from MicroEnergy Technologies, Vancouver WA), which serve as concentrators. Thus, applying THz electronic systems as broadband, standoff sensors will be enabled by the benefits gained from new antennas and optical arrangements.





Figure 1. Reflection setup for measuring absorption of bacterial spore samples.



<i>B. cereus</i> (BC)	85
<i>B. globigii</i> (BG)	76
<i>B. thurengiensis</i> (BT)	33

Figure 2. Picture of sample holder and list of bacterial spores measured with the sample masses in mg.




Figure 3. Results of broadband reflection measurements from samples detailed in Fig. 2. Ten trials were conducted on each sample; the error bars show +/- one standard deviation. Note that distinguishability of samples increases at higher frequencies.

We conducted several reflection measurements of bacterial spore samples, first using 33-85 mg masses on a highly-reflective mirrored surface (Figures 2-3), then using  $< 10 \mu\text{g}$  masses on optical micropillars (Figures 4-5). We note that in both cases, we could distinguish among the variety of spores when using a broadband reflection technique, though with three orders of magnitude reduction in sample mass, the limits of distinction were being reached (Figure 5).




Figure 4. Micropillar array mounted on glass slide (inset: close-up of array), with list of bacterial spore types and mass in  $\mu\text{g}$ .




Figure 5. Results of broadband reflection measurements from samples detailed in Fig. 4. Ten trials were conducted on each sample; the error bars show  $\pm$  one standard deviation. Note that distinguishability of samples is less than that possible with greater sample masses (Figure 3).

### Personnel supported

Name	Function	Honors	Awards	Degrees
Van der Weide, Daniel	PI	None this term	None this term	N/A
Choi, Min	Grad student	None this term	None this term	Ph.D. (finishing this year)
Sun, Kae-Oh	Grad student	None this term	None this term	Ph.D. (finishing this year)
Kelvin Fu	Post-doctoral researcher	None this term	None this term	Ph.D.
Alexander Kozyrev	Post-doctoral researcher	None this term	None this term	Ph.D.
Charles Paulson	Post-doctoral researcher	None this term	None this term	Ph.D.
Taylor, Kimberly	Grad student	None this term	None this term	Ph.D.
Bettermann, Alan	Researcher	None this term	None this term	N/A

### Publications

(a) Manuscripts submitted, but not published

(NONE)

(b) Papers published in peer-reviewed journals

A. B. Kozyrev, H. J. Kim, A. Karbassi, and D. W. van der Weide, "Wave Propagation in Nonlinear Left-Handed Transmission Line Media," *Applied Physics Letters*, vol. 87, pp. 121109-11, 2005.

A. B. Kozyrev and D. W. van der Weide, "Nonlinear Wave Propagation Phenomena in Left-Handed Transmission Line Media," *IEEE Transactions on Microwave Theory and Techniques*, vol. 53, pp. 238-45, 2005.

H. J. Kim, A. B. Kozyrev, A. Karbassi, and D. W. van der Weide, "Linear Tunable Phase Shifter Using a Left-Handed Transmission Line," *IEEE Microwave and Wireless Component Letters*, vol. 15, pp. 366-68, 2005.

A. B. Kozyrev and D. W. van der Weide, "Explanation of the Inverse Doppler Effect Observed in Nonlinear Transmission Lines," *Physical Review Letters*, vol. 94, pp. 203902-6, 2005.

K. M. Taylor and D. W. van der Weide, "Ultra-Sensitive Detection of Protein Thermal Unfolding and Refolding Using Near-Zone Microwaves," *IEEE Transactions on Microwave Theory and Techniques*, vol. 53, pp. 2441, 2005.

X. Li, M. Choi, S. C. Hagness, and D.W. van der Weide, "Numerical and experimental investigation of an ultrawideband ridged pyramidal horn antenna with curved launching plane for pulse radiation," *IEEE Antennas and Wireless Propagation Letters*, vol. 2, pp. 259-262, 2003.

S. Ali, S. Malu, D. McCammon, K.L. Nelms, R. Pathak, P.T. Timbie, and D.W. van der Weide, "Antenna-coupled transition-edge hot-electron microbolometer," *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, vol. 520, pp. 490-492, 2004.

(b) Papers published in non-peer-reviewed journals or in conference proceedings

K. Taylor and D.W. van der Weide, "Ultra-Sensitive Microwave Detection of Protein Conformational Changes," *IEEE MTT-S Int. Microwave Symp. Dig.*, Vol 3, 1583 (2004).

(c) Papers presented at meetings, but not published in conference proceedings

D. W. van der Weide, "Antennas and electronics for sub-THz stand-off spectroscopic imaging,"  
**Invited Presentation** at University of Adelaide, December 2004.

## Interactions/Transitions

*Participation at meetings:* Invited to and participated in Terahertz review at University of Adelaide, December 2004.

*Consultative and advisory functions:* none during the period

*Transitions:* Our technology is being transitioned to a startup company, Tera-X, LLC.

*New discoveries:* (none this year).

*Honors/Awards:* none during the period

## References

- [1] M. K. Choi, K. Taylor, A. Bettermann, and D. W. van der Weide, "Broadband 10-300 GHz stimulus-response sensing for chemical and biological entities," *Physics in Medicine and Biology*, vol. 47, pp. 3777, 2002.
- [2] M. K. Choi, A. Bettermann, and D. W. van der Weide, "Biological and chemical sensing with electronic THz techniques," presented at Optical Technologies for Industrial, Environmental, and Biological Sensing, Providence, RI, 2003.
- [3] M. K. Choi, K. Taylor, A. D. Bettermann, and D. W. van der Weide, "Spectroscopy with electronic terahertz techniques for chemical and biological sensing," in *Emerging Scientific Applications and Novel Device Concepts, THz sensing technology*, vol. II, D. L. Woolard, M. S. Shur, and W. R. Loerop, Eds., 2003.
- [4] M. K. Choi, A. D. Bettermann, and D. W. van der Weide, "Potential for detection of explosive and biological hazards with electronic terahertz systems," *Philosophical Transactions Royal Society London*, vol. A 362, pp. 337-349, 2004.
- [5] D. W. van der Weide, M. Choi, K. Taylor, and A. Bettermann, "Sensing biomolecules with microwave and terahertz frequencies," presented at EMC Zürich, 2005.
- [6] J. S. Bostak, D. W. van der Weide, D. M. Bloom, B. A. Auld, and E. Özbay, "All-electronic terahertz spectroscopy system with terahertz free-space pulses," *Journal of the Optical Society of America B*, vol. 11, pp. 2561-2565, 1994.
- [7] J. S. Bostak, D. M. Bloom, D. W. van der Weide, B. A. Auld, and E. Özbay, "All-electronic generation and detection of terahertz free-space pulses and their application to a terahertz spectroscopy system," presented at Millimeter and Submillimeter Waves, San Diego, 1994.
- [8] D. M. Bloom, J. S. Bostak, D. W. van der Weide, B. A. Auld, and E. Özbay, "All-electronic generation and detection of terahertz free-space pulses and their application to a terahertz spectroscopy system," presented at Nonlinear Optics for High-Speed Electronics and Optical Frequency Conversion, Los Angeles, 1994.
- [9] D. W. van der Weide, J. S. Bostak, B. A. Auld, and D. M. Bloom, "All-electronic generation of 880 fs, 3.5 V shockwaves and their application to a 3 THz free-space signal generation system," *Applied Physics Letters*, vol. 62, pp. 22-24, 1993.
- [10] D. W. van der Weide, J. S. Bostak, B. A. Auld, and D. M. Bloom, "All-electronic free-space picosecond pulse generation and detection," *Electronics Letters*, vol. 27, pp. 1412-1413, 1991.
- [11] K. M. Taylor and D. W. van der Weide, "Ultra-Sensitive Detection of Protein Thermal Unfolding and Refolding Using Near-Zone Microwaves," *IEEE Transactions on Microwave Theory and Techniques*, vol. 53, pp. 2441, 2005.
- [12] A. B. Kozyrev, H. J. Kim, A. Karbassi, and D. W. van der Weide, "Wave Propagation in Nonlinear Left-Handed Transmission Line Media," *Applied Physics Letters*, vol. 87, pp. 121109-11, 2005.
- [13] A. B. Kozyrev and D. W. van der Weide, "Nonlinear Wave Propagation Phenomena in Left-Handed Transmission Line Media," *IEEE Transactions on Microwave Theory and Techniques*, vol. 53, pp. 238-45, 2005.
- [14] H. J. Kim, A. B. Kozyrev, A. Karbassi, and D. W. van der Weide, "Linear Tunable Phase Shifter Using a Left-Handed Transmission Line," *IEEE Microwave and Wireless Component Letters*, vol. 15, pp. 366-68, 2005.
- [15] A. B. Kozyrev and D. W. van der Weide, "Explanation of the Inverse Doppler Effect Observed in Nonlinear Transmission Lines," *Physical Review Letters*, vol. 94, pp. 203902-6, 2005.